

## ISUZU 3tons ice cream truck

### Specification:

ISUZU ice cream truck		
General	Chassis Brand	ISUZU
	Overall Dimension	5995X2250X3200 mm
	GVW / Kerb Weight	7,360kg / 3,500kg
Cab	Cab Capacity	2 persons allowed
	Air Conditioner	Heating/cooling air conditioner
Engine	Fuel Type	Diesel
	Engine Brand	4KH1CN6LB
	Power	120 HP (88 KW)
	Displacement	2999ml
	Emission Standard	Euro VI
Chassis	Drive Type	4X2 (left hand drive)
	Transmission	ISUZU MSB 5-shift speed levers with 1 reverse
	Wheelbase/No. of axle	3360 mm / 2
	Tire Specification	7.00R16
	Tire Number	6 tires and 1 spare tire
	Max Speed	100 km/h
	Paint	Metallic paint
Superstructure	Body size	4000×2000×2000(mm)
	Load Capacity	3.5 Tons
	Panel Structure	Fiber glass sandwich polyurethane
	Front/Side/Rear panel	Panel Thickness: 80mm
	Roof/Floor panel	Panel Thickness: 105mm
	Lights & Switch	Led, Water-proof, 12V/24V convertible
	Lowest temperature	USA Carrier -30℃ 400H
Equipment	FRP inside and outside the box, 12cm high-density thermal insulation board, the bottom plate is anti-slip patterned aluminum plate, and the rear door lock is stainless steel.	
	There are 4 doors on the left and right sides, and stainless steel shelves are added inside the box.	